



Technical drawing of a square base plate. The drawing shows a square plate with a side length of 180. It features a central circular hole with a diameter of $\varnothing 200$. Surrounding the central hole are eight smaller circular holes, each with a diameter of $\varnothing 230$. The mounting holes are specified as 4-M12x28. The corners of the plate are chamfered at a 45° angle.



1. 本产品应放在干燥的环境中保管
2. 若放在室外或有潮气的场所保管时, 应装入箱内用塑料袋严密包裹, 以免受雨淋或外气的侵蚀。
3. 本产品为精密件, 安装时应小心装入, 严禁敲打。并用扭力扳手对孔位螺栓进行锁紧。

客户签字 Customer's Signature	速 比 Ratio	3-20	运转效率 Transmission Efficiency	93%	扭转刚度 Torsional Rigidity	140N.m/arcmin	公司名称 Company name	 锋桦 [®] 锋桦传动科技(江苏)有限公司 锋桦传动设备(上海)有限公司 台灣 鋒 桦 科 技 有 限 公 司
	额定扭矩 Rated Torque	900-1250N·m	精度寿命 Service Life	20000Hrs	单位 Unit	mm		
	最大扭矩 Max.Torque	2700-3750N·m	噪音 Noise	72dB	比例 Proportion	1:1	图名 Drawing name	行星减速机Planetary gearbox: PAR180-L1-S2-P1
	额定输入转速 Rated Input speed	2000rpm	环境温度 Enviromental Temperature	-15°-- +90°	版本 Version	最新版本 Latest version	服务热线 Service hotline	400-8040-668 / QQ:4008040668
	最大输入转速 Max.inputspeed	4500rpm	惯量 Inertia	22.51-28.98kg.cm ²	日期 Date	2023/08/22	网址/邮箱Website/email	www.fht.tw / www.3fgearmotor.com fht@fht.tw / sales@3fgearmotor.com
	回程间隙 Backlash	≤8arcmin	重量 Weight	51Kg	设计 Design刘建勇	设计 X3	电话/传真Tel/Fax	021-39948832 /021-39948836